

#### **Touring Series**

Full-range 3,5" Miniature loudspeaker

### **Audio-Performance Qube3-Pro**

The Qube3-Pro loudspeaker is a miniature, compact, widerange loudspeaker for high quality distributed sound system applications.

the Qube3-Pro connects directly to the amplifier and is capable of producing high sound pressure levels while dramatically reducing distortion and easing installation requirements.

The Qube3-Pro comprises a single 3.5-inch cone driver with a 8 ohm voice coil mounted in a sealed enclosure. The Qube3-Pro draws 110 watts peak from the line, and produces 110.5 dB peak SPL.

Typically, with four Qube3-Pro connected in parallel on the line, the system requires a direct drive power amplifier capable of 315 watts continuous output (25 volts RMS) into 2 ohms.

Our professional digital amplifiers AP5000 or AP48M3 must be used to protect your Qube3-Pro loudspeaker against damaging overload conditions, while ensuring that they meet their published specifications.

When multiple Qube3-Pro are used in parallel, a switcheable 1KOhm,100V Line transformer in conjonction with the AP5000 or AP48M6 set in bridge mode configuration, allow the user to drive up to 250 RubiQ-Pro.

Two connector versions are available: the sealed EN3 connector for outdoor installations, and a Phoenix-style keyed connector for indoor use.

# **DESIGNED FOR**

High-quality distributed systems, paging and music

Museums
Clubs
Bars
Corporate boardroom



# **Special Features**

**Ultra-Compact** 

Full-range

Low distrotion

Switcheable 8 Ohm / 1 KOhm Impedance

Color matching available



## RubiQ\_Pro Specifications

#### ACOUSTICAL WITH AUDIO-PERFORMANCE AP5000 or AP48M3 Digital Amplifier

 Maximum peak SPL (2)......
 110.5dB

 Directivity H x V ......
 100° x 100°

 Power handling ......
 110W (AES) (4)

**TRANSDUCERS** 3,5 inch, low distortion, long excursion

Nominal impedance ...... 8 Ohms / 1KOhm

**ELECTRICAL** 

wired in parallel

**MECHANICAL** 

Mounting ...... 1,5kg

2x M8 side inserts







